

Flexible edge protection lash.straps(4x)

Material no.: 1000001870 | Matchcode: ZFKS ZG VPE4 | EAN code: 4045294230999



- » flexible plastic edge protection profile
- » protects the load
- » prevents shifting of lashing belts
- » maximum belt width 35 mm
- » saves time and money

Materials & Colour

Material:	Synthetic material PA6 Polyester Steel
Colour:	Blue

Dimensions

External dimensions:	180 x 75 x 7 mm
----------------------	-----------------

Technical details

Weight:	0,11 kg
---------	---------

Accessories

	Material no.	Description	Matchcode	EAN code
--	--------------	-------------	-----------	----------



1000001736	ProSafe individual lashing point restraint pole	EZ S PS	4045294228040
------------	---	---------	---------------

Flexible edge protection lash.straps(4x)

Material no.: 1000001870 | Matchcode: ZFKS ZG VPE4 | EAN code: 4045294230999

	Material no.	Description	Matchcode	EAN code
	1000001870	Flexible edge protection lash.straps(4x)	ZFKS ZG VPE4	4045294230999
	1000003736	ProSafe CargoStopp	CST PS	4045294403072
	6000001231	ProSafe individual lashing point	EZ PS	4045294224646
	6000001259	ProSafe floor lashing point	BZ PS S	4045294225179
	6000001260	ProSafe floor lashing point restraint pole	BZ SP PS	4045294225186
	6000001116	Anti-rattle mat 750x500	ARM 750X500	4045294239565

Description

The flexible plastic edge protection profile protects both the load as well as the lashing belt when transporting goods with sharp edges. Furthermore the lashing belt is guided through the edge protection profile, which in turn prevents shifting of the lashing belt. This simple aid to professional load securing should not be absent in any LCV! In end effect it simplifies the work process, protects your lashing belts and your valuable load, which in turn saves you time and money. The maximum belt width is 35 mm

We reserve the right to make changes in the interest of technical progress, as well as correcting printing errors and mistakes. Pictures are similar, decorative material not included. With the publication of this data sheet, previous editions lose their validity. Version: 29.02.2024