Data sheet



ProSafe CargoStopp

Material no.: 1000003736 | Matchcode: CST PS | EAN code: 4045294403072



- » enables form-fitting load securing
- » inserted in floor lashing point
- contains an integrated lashing point
- » can be screwed on with a restraint pole

Materials & Colour

Material: Steel
Colour: Silver

Dimensions

External dimensions: 64 x 40 x 120 mm

Technical details

Weight: 0,21 kg

Accessories				
	Material no.	Description	Matchcode	EAN code
	1000020089	Aluminum locking beam 1880x34x32mm	ASB 1880X34X32	4014599014962
40	1000000222	ProSafe lashing belt clamp buckle 3 m	PSH KS 3	4045294195892



ProSafe CargoStopp

Material no.: 1000003736 | Matchcode: CST PS | EAN code: 4045294403072

Material no.	Description	Matchcode	EAN code
1000000223	ProSafe lashing belt clamp buckle 6 m	PSH KS 6	4045294195908
1000000224	Lashing strap ProSafe clamping lock 1.4 m, 250 daN	PSH KS 1,4	4045294195915
1000000225	ProSafe lashing belt ratchet 3.5 m	PSH RA 3,5	4045294195922
1000000226	ProSafe lashing belt ratchet 6 m	PSH RA 6	4045294195939
801012139	ET Kit restraint pole aluminium	ET ZSPALUB	4045294144883

Description

The ProSafe CargoStopp in combination with the Sobogrip ProSafe floor for form-fitting load securing. It is inserted in the ProSafe floor lashing point and contains an integrated lashing point. Therefore the lashing strap can be directly hooked-in to the CargoStopp and therefore you save on an additional floor lashing point. The CargoStopp ProSafe has a locking function in addition, which prevents the CargoStopp from unintentionally slipping out of the floor lashing point. The ProSafe CargoStopp therefore enables quick and professional load securing. In order to have a permanent stop bar on the floor, the ProSafe CargoStopp can have a restraint pole screwed on to it.

We reserve the right to make changes in the interest of technical progress, as well as correcting printing errors and mistakes. Pictures are similar, decorative material not included. With the publication of this data sheet, previous editions lose their validity. Version: 29.02.2024