

### ProSafe Load securing net 1775x1150

Material no.: 1000001306 | Matchcode: ZLSN 1,7X1,1 PS | EAN code: 4045294213329



- » particularly suitable for loads that are difficult to secure, odd-shaped or round
- » numerous fixing options
- » tested in accordance with Guideline VDI 2700 Sheet 3.3
- » has a bearing load of up to 400 daN
- » four lashing straps with ratchet, two with clamping lock

#### Materials & Colour

Material:	PA6 Polyester Steel
Colour:	Anthracite

#### Dimensions

External dimensions:	1.775 x 1.150 x 30 mm
Length in mm:	1775x1150

#### Technical details

Weight:	4,40 kg
Maximum tensile force in daN:	400

### ProSafe Load securing net 1775x1150

Material no.: 1000001306 | Matchcode: ZLSN 1,7X1,1 PS | EAN code: 4045294213329

#### Description

The ProSafe load securing net secures your valuable freight and is especially ideal for hard to secure, non-form fitting or even round cargo. Thanks to the ProSafe System, the net can be hooked-in to the ProSafe uprights and cross members of the Globelyst van racking system and Sortimo HD, to lashing tracks, to the Sobogrip ProSafe floor or even to the original lashing points of the vehicle. This means you always have a suitable lashing point handy and you are completely flexible in your operations, which in turn means you save time while securing your load professionally.

The net is extremely robust, tear-proof and is manufactured only from first class materials meaning it boasts an extremely long service life. The mesh size comprises 120 x 120 mm with a belt width of 25 mm. On the net you have four lashing belts with ratchet buckles and two with clamp buckles. The load securing net is delivered in a handy cloth bag.

The quality and functionality of the load securing nets have been tested and certified by Dekra in compliance with the regulation VDI 2700 page 3.3. The resilience of up to 400 daN is also tested and has received its certification from Dekra - so you can rely on a long and functional usage of your ProSafe load securing nets. And even better, the flexibility of the ProSafe Systems additionally saves you a huge amount of time when securing your load.

We reserve the right to make changes in the interest of technical progress, as well as correcting printing errors and mistakes. Pictures are similar, decorative material not included. With the publication of this data sheet, previous editions lose their validity. Version: 21.12.2023