

Telescope restraint poles 1700-2200mm ProSafe

Material no.: 1000018968 | Matchcode: SPT 170-220 PS | EAN code: 4014599250513



- » Ease of operation
- » Large adjustment range
- » Integrated ProClick interfaces
- » Compatible with the ProSafe load securing system
- » Plastic protective sleeve

Materials & Colour

Material:	Aluminium, Steel, Synthetic material
Colour:	Blue




Dimensions

External dimensions:	1.741 x 63 x 58 mm
Length in mm:	1700

Technical details





Weight:	4,10 kg
Maximum tensile force in daN:	300

Accessories

	Material no.	Description	Matchcode	EAN code
	6000015240	ProClick Tool Card S 6	PC WKZK S 6	4014599453525
	6000015241	ProClick hammer holder S	PC HH S	4014599453549
	6000013929	ProClick Nail bag M	PC NT M	4014599386373

Telescope restraint poles 1700-2200mm ProSafe

Material no.: 1000018968 | Matchcode: SPT 170-220 PS | EAN code: 4014599250513

	Material no.	Description	Matchcode	EAN code
	6000013928	ProClick Tool Bag M 14	PC WKZT M 14	4014599386366
	6000013930	ProClick Tool Bag L 16	PC WKZT L 16	4014599386380
	6000013931	ProClick Tool Bag L 36	PC WKZT L 36	4014599386830
	6000013932	ProClick Tool Bag L 39	PC WKZT L 39	4014599386847

Description

The total length of the telescopic restraint pole can be variably adjusted between 1700 mm and 2200 mm. It features ProSafe end fittings and can therefore be used in ProSafe lashing rails and all SoboPro LSC floors.

We reserve the right to make changes in the interest of technical progress, as well as correcting printing errors and mistakes. Pictures are similar, decorative material not included. With the publication of this data sheet, previous editions lose their validity. Version: 04.09.2025